



DR. BABASAHEB AMBEDKAR TECHNOLOGICAL UNIVERSITY, LONERE
At. Po. Lonere, Tal. Mangaon, Dist. Raigad 402 103 MS (www.dbatuonline.com)

INVITATION FOR QUOTATION

Our Ref No. : DBATU/Store /Mech. Engg & Physics./Material /2021/

Date: 28/09/2021

Quotation For: Material of Science and Maetallurgy Laboratory and Physics

Due On: 11/10/2021

Date of Opening: 12/10/2021

Time: 11:00 am

To,

Sub: QUOTATION FOR THE SUPPLY OF STORE

Dear Sir,

Your quotation for the items listed overleaf, may please be submitted to the under signed, so as to reach this Office not later than 11/10/2021

While submitting your quotation, the following procedure may please be observed and other points borne in mind.

1. The maker's name must be specified.
2. The "Terms and Conditions" for supply and delivery of stores, should be clearly indicated in the quotation, stating whether rates are, inclusive of all taxes, Packing and forwarding charge,s Freight charges, etc. or not, however rates offered as including all taxes will be more welcome.
3. If packing and forwarding charges are to be charged separately, it should be so clearly stated in your quotation.
4. Please mention clearly whether consignment would be Ex-Godown, Ex-Shop, of F.O.R. dispatching stations. Preferably terms offered as "Delivery of consignment of stores, on F.O.R.
5. Envelope should be super-scribed "**Quotation for reference No..... of dated.....**" It should also be superscripted as per the format given above.
6. The quotation would be opened as per date and timing given above, if desired by you, you may depute an authorized representative with a letter of authority to be present at the time of opening of the quotation at this Office on the aforesaid day, date & time.
7. Your quotation must be valid for a minimum 30 (Thirty) working days from the date of it's opening.
8. Quotation received after the date of opening may not be taken into consideration.
9. Items tendered should confirm to the specification shown in the attached list when and where, full or no specifications are indicated against items in the list. Kindly furnish your full specification in accordance with accepted standards against each item tendered. Where reference to catalogue is made, the relevant catalogues/ Pamphlets/ Literature should accompany the quotation.
10. Your quotation should be for all new items and not for second1 hand.
11. Please state whether items will be available Ex-Stock. If not the minimum period for delivery, or for supplying the items or stores.

12. It should be clearly stated whether **GST**, Insurance, Freight or packing and forwarding charges, or any other taxes and duties, etc. leviable.
13. It would be appreciated if illustrated catalogues/Literature etc is furnished with the quotation.
14. Expression to as "Complete with standard Equipment" complete with standard accessories "Equipment to" As good as should be avoided. If at all their use is unavoidable then it should be very specifically indicated as to what exactly they mean and what exactly would be supplied under them. Any ambiguity or vagueness should be avoided.
15. For convenience, kindly adopt while quoting the same serial Nos. as given in the list detailed below.

Thanking You. /

Yours faithfully,


Registrar

Dr. Babasaheb Ambedkar Technological University, Lonere

List of Items

Sr. No.	Description	Make	Approx. Qty Req.	Rate per / Each / Unit	Remarks
1	Rockwellcum-Brinell Hardness Tester : Max Test Height : 295mm; Depth of Throat : 148mm; Size of Base : 475x 220mm; Height of Machine : 865mm Net Weight : 125Kg; Load Setting : Externally Manual. Test Loads: 60,100,150, 187.5 & 250 Kgf Initial Load : 10 kg. With Accessories: Testing Table – 50mm Flat Testing Table – V-38mm; Test Block – 02 Nos; Brinell Microscope 01; Manual Allen Key Set With all accessories		01		
2	Electromagnetic yoke: Current input 110V/220V, single Phase, current drawn 25A (max load condition); Portable & light weight - only 4 Kgs. Strength= More than 4.5Kg in AC and 18.1 Kg in DC max at 140mm pole spacing; No risk of current flowing through the component being tested. No risk of 'sparking' or 'hot spots' on the job. Low power consumption. Solid-state control PCB mounted inside Yoke. It comes with the choice of „AC“ for open surface flaw detectability and „H.W.D.C“ for surface or sub-surface flaw detect-ability. Articulated legs to suit differing component contours. Interpole distance adjustable upto 12" (300mm). Potentiometer is used for adjustment of DC magnetic field. With all accessories		01		

3	Erichsen cupping tester : Thickness of sample- 0.1-2mm; Least Count- 0.01mm; Overall Dimension- 400× 500× 500; Lab Hand Operated		01		
4	Jominy End Quench Test Apparatus : SS body, Automation Grade: Semi-Automatic Frequency: 60 Hz Temperature Range: 0 to 65 Degree C Operating Voltage: 220 V		01		

- Quantity may vary