

INVITATION FOR QUOTATION

11 JAN 2024

Our Ref No. : DBATU/Store/Security/University Sound System /2024/144 Date: 09/01/2024

Quotation For: University Sound system and auxiliary Due On: 22/01/2024

Date of Opening: 23/01/2024 Time: 11.00 am

=====

To,

Sub: QUOTATION FOR THE SUPPLY OF STORE

Dear Sir,


Your quotation for the items listed overleaf, may please be submitted to the under signed, so as to reach this Office not later than 22/01/2024

While submitting your quotation, the following procedure may please be observed and other points borne in mind.

1. The maker's name must be specified.
2. The "Terms and Conditions" for supply and delivery of stores, should be clearly indicated in the quotation, stating whether rates are, inclusive of all taxes, Packing and forwarding charge,s Freight charges, etc. or not, however rates offered as including all taxes will be more welcome.
3. If packing and forwarding charges are to be charged separately, it should be so clearly stated in your quotation.
4. Please mention clearly whether consignment would be Ex-Godown, Ex-Shop, of F.O.R. dispatching stations. Preferably terms offered as "Delivery of consignment of stores, on F.O.R.
5. Envelope should be clearly marked with our reference No and date of this quotation. It should also be superscripted as per the format given above.
6. The quotation would be opened as per date and timing given above, if desired by you, you may depute an authorized representative with a letter of authority to be present at the time of opening of the quotation at this Office on the aforesaid day, date & time.
7. Your quotation must be valid for a minimum 30 (Thirty) working days from the date of it's opening.
8. Quotation received after the date of opening may not be taken into consideration.
9. Items tendered should confirm to the specification shown in the attached list when and where, full or no specifications are indicated against items in the list. Kindly furnish your full specification in accordance with accepted standards against each item tendered. Where reference to catalogue is made, the relevant catalogues/ Pamphlets/ Literature should accompany the quotation.
10. Your quotation should be for all new items and not for second hand.
11. Please state whether items will be available Ex-Stock. If not the minimum period for delivery, or for supplying the items or stores.

12. It should be clearly stated whether **GST**, Insurance, Freight or packing and forwarding charges, or any other taxes and duties, etc. leviable
13. It would be appreciated if illustrated catalogues/Literature etc is furnished with the quotation.
14. Expression to as "Complete with standard Equipment" complete with standard accessories "Equipment to" As good as should be avoided. If at all their use is unavoidable then it should be very specifically indicated as to what exactly they mean and what exactly would be supplied under them. Any ambiguity or vagueness should be avoided.
15. A Declaration in form I will be issued for 8% sales Tax concession for sales of scientific instruments by a registered dealer, as per Provision made, under Bombay, Sales Tax-Act-1959, vide Section 41, at entry No – 1095/37/Taxation 2, dated 22 nd September,1935. If a change in declaration in form I will be issued according to the instruction issued by the Maharashtra Govt time to time.
16. For convenience, kindly adopt while quoting the same serial Nos. as given in the list detailed below.

Thanking You.








Yours faithfully,


Registrar
Dr. Babasaheb Ambedkar Technological University, Lone

List of Items

Sr. No.	Description / Specification	Make	Approx. Qty Req.	Rate per Unit
01	As per Annexure 'A'			

Annexure-A

S/N	Equipment	Specification	Qty	Make
1	<p>WIRELESS DUAL LAPEL MICROPHONE</p> 	<p>Technical Details Product Dimensions 2.54 x 6.35 x 10.16 cm; 80 Grams Batteries 1 9V batteries required. Item model number PRO88W-R35 Compatible Devices Camcorder Connector 3.5 month Jack Material velcro Hardware Platform camcorder, camera, computer Power Source Battery Powered Item Weight 80 g Manufacturer audio-technica</p>	1	AUDIO TECHNICA/JBL/Sony/Pioneer
2	<p>WIRELESS DUAL HAND MICROPHONE</p> 	<p>Key Features For Presenters and Performers Rugged Handheld Transmitter True-Diversity Rackmount Receiver 2395 Auto-Scan Frequencies Selectable 10/30mW RF Power Interchangeable Capsule Design Dual-Mode OLED Display 9.5 Hours on NiMH Batteries Expandable to 40 Mic Channels/330' Range</p>	2	AUDIO TECHNICA/JBL/Sony/Pioneer
3	<p>HANDHELD WIRED MICROPHONE</p>  <p>24 Carat gold-plated XLR Connector</p>	<p>AKG Vocal Dynamic Microphone, Super-Cardioid, Black General Specifications Audio frequency bandwidth 40 - 20000 Hz Sensitivity 2.5 mV/Pa Electrical impedance 580 Ohms Recommended load impedance 2000 Ohms Polar Pattern Supercardioid Dimensions Length 190 mm Diameter 51 mm Net Weight 320 g</p>	2	AKG/JBL/Sony/Pioneer
4	<p>12 CHANNEL MIXING CONSOLE</p> 	<p>FEATURES 12-Channel Mixing Console Max. 6 Mic / 12 Line Inputs (4 mono + 4 stereo) 2 GROUP Buses + 1 Stereo Bus 2 AUX (incl. FX) "D-PRE" mic preamps with an inverted Darlington circuit 1-Knob compressors PAD switch on mono inputs +48V phantom power XLR balanced outputs Internal universal power supply for world-wide use Optional Rack Mount Kit RK-MG12 Available Metal chassis 308 mm x 118 mm x 422 mm (12.1" x 4.6" x 16.6")</p>	1	YAMAHA MG12/JBL/Sony/Pioneer
5	<p>8 INCH 200 WATT SPEAKER</p> 	<p>Speaker GS PRO 8inc PHL 76 200W 25% more Loudness 8 Ohm Impedance Aluminium Frame 3 VC 9.5 Kg Weight 45-3.5 KHz Frequency Range #Best Quality PA Speaker Systems Professional 2-way speaker system with exceptional efficiency, long throw and unmatched intelligibility of sound. It consists of two 15" high performance full range dual cone speakers and a High frequency compression driver. The speaker system is housed in an acoustically treated Bass Reflex Trapezoidal with durable paint finish enclosure. The cabinet has been fitted with heavy-duty handles to allow ease of transportation and a strong steel grille for speaker protection. Ideal for both indoor and outdoor sound reinforcement applications. Specially designed for Auditoriums and DJs.</p>	4	GS PRO/JBL/Sony/Pioneer
6	<p>500 WATT PASSIVE SUBWOOFER</p> 	<p>SPECIFICATIONS: System Type 15", subwoofer system. Max SPL Output 98 dB. Frequency Range (30dB) 30Hz – 250 Hz. Frequency Response (-3 dB) 35 Hz – 120 Hz. Dimensions. (H x W x D) 22.62 x 26.92 x 26.89 (in) Net Weight 39.5 kg (87 lb) 15-Inch Subwoofer, 1000W rms The gs audio 15-Inch front loaded lf driver Subwoofer is a premium quality 500w subwoofer loudspeaker ideal for medium sized venues, touring musicians and DJ's. With innovative new technology have provided a high performance subwoofer that incorporates a custom designed 15 inch and advanced and detailed user assignable.</p>	1	GS PRO/JBL/Sony/Pioneer
7	<p>POWER AMPLIFIER</p>	<p>Two-channel, 1500W @ 4Ω Power Amplifier Features Peakx Plus™ Limiters provide the ultimate in system performance and protection by allowing full control over threshold, attack, and release Enhanced Subharmonic Synth section provides user control over frequency, gain and filter type for system-specific tuning. 3 User-defined fan mode controls – normal, early and fullspeed – for matching fan performance to a specific application. New system monitoring provides software visibility of AC line voltage and power supply temperature Integrated cast-aluminum handles for easy handling and enhanced</p>	1	GS PRO/JBL/Sony/Pioneer

		<p>durability. Locking power cord clip provides a secure connection between the amplifier and power cord</p> <p>Updated HiQnet System Architect™ control software Increased number of presets to a total of 50; 49 of which are user definable</p>		
8	<u>AUDIO SPEAKER CABLE 100 METER</u>	Speaker Cable 2 Core dual pvc coated, pure copper/ CABLE/100M / OFC 99.999% Resistance :0.013/m, Capacitance: 55,530 pf /m Sectors: 2x1 5mm2 Conducteur Prograde (Tinned) ,no signal losses at longdistances.	100	PRIME/JBL/Sony/Pioneer
09	<u>AUDIO SIGNAL CABLE</u>	2-conductor Shielded Cable with 24AWG stranded high conductivity tinned copper conductors and a high density polyethylene insulation. The 9452 series multi-conductor low-impedance cable comes with Beldfoil® aluminum foil-polyester tape outer shield, a 24AWG stranded tinned copper outer shield drain wire and a black PVC outer jacket.	50	BELDEN/JBL/Sony/Pioneer
10	<u>CONNECTORS AND ASSESORIES</u>	Cables, Connectors and Accessories (Lumpsum)	13	NEUTRIK/JBL/Sony/Pioneer
11	<u>SPEAKER STAND</u>	Floor Mount Speker Stand for Speakers.	4	GS PRO/JBL/Sony/Pioneer