

DR. BABASAHEB AMBEDKAR TECHNOLOGICAL UNIVERSITY, LONERE

At. Po. Lonere, Tal. Mangaon, Dist. Raigad 402 103 MS (www.dbatu.in)

INVITATION FOR QUOTATION

0 3 OCT 2024

Our Ref No.: DBATU/ Store/Polymer & Plastic/ Basic Pneumatic Trainer Kit/2024/2889

Date: 03 / 10/2024

Due On: 15/10/2024

Time: 12.30 pm

Quotation For: Basic Pneumatic Trainer Kit

Date of Opening: 14 / 10/2024

To,

Sub: RE-QUOTATION FOR THE SUPPLY OF STORE

Dear Sir,

Your quotation for the items listed overleaf, may please be submitted to the under signed, so as to reach this Office not later than \5 / 10/2024

While submitting your quotation, the following procedure may please be observed and other points borne in mind.

- 1. The maker's name must be specified.
- 2. The "Terms and Conditions" for supply and delivery of stores, should be clearly indicated in the quotation, stating whether rates are, inclusive of all taxes, Packing and forwarding charges Freight charges, etc. or not, however rates offered as including all taxes will be more welcome.
- 3. If packing and forwarding charges are to be charged separately, it should be so clearly stated in your quotation.
- 4. Please mention clearly whether consignment would be Ex-Godown, Ex-Shop, of F.O.R. dispatching stations. Preferably terms offered as "Delivery of consignment of stores, on F.O.R.
- 5. Envelope should be super-scribed "Quotation for reference No...... of dated....." It should also be superscripted as per the format given above.
- 6. The quotation would be opened as per date and timing given above, if desired by you, you may depute an authorized representative with a letter of authority to be present at the time of opening of the quotation at this Office on the aforesaid day, date & time.
- 7. Your quotation must be valid for a minimum 30 (Thirty) working days from the date of it's opening.
- 8. Quotation received after the date of opening may not be taken into consideration.
- 9. Items tendered should confirm to the specification shown in the attached list when and where, full or no specifications are indicated against items in the list. Kindly furnish your full specification in accordance with accepted standards against each item tendered. Where reference to catalogue is made, the relevant catalogues/ Pamphlets/ Literature should accompany the quotation.
- 10. Your quotation should be for all new items and not for second hand.
- 11. Please state whether items will be available Ex-Stock. If not the minimum period for delivery, or for supplying the items or stores.
- 12. It should be clearly stated whether GST, Insurance, Freight or packing and forwarding charges, or any other taxes and duties, etc. leviable.
- 13. It would be appreciated if illustrated catalogues/Literature etc is furnished with the quotation.

- 14. Expression to as "Complete with standard Equipment" complete with standard accessories "Equipment to" As good as should be avoided. If at all their use is unavoidable then it should be very specifically indicated as to what exactly they mean and what exactly would be supplied under them. Any ambiguity or vagueness should be avoided.
- 15. For convenience, kindly adopt while quoting the same serial Nos. as given in the list detailed below,

Thanking You.

Yours tithfully,

Registrar

Dr. Babasaheb Ambedkar Technological University, Lonere

List of Items

Sr. No.	Description	Make	Approx. Qty Req.	Rate per / Each / Unit	Remarks
01	Basic Pneumatic Trainer Kit Specification As per Annexure 1		01		

Quantity may vary

Annexure 1

1 Trolley with Caster wheels 2 Quick Push-Pull connection 3 High Pressure Tubing (PU6) 5 5/2 way lever operated valve 5 5/3 way Lever operated DC valve 6 Pressure Gauge 21/2" Dial 7 5/2 way Single Pilot operated Direction control valve 8 5/2 way Double pilot operated Direction control valve 9 AND Gate valve 10 OR Gate valve 11 Time delay valve 12 Quick exhaust valve 13 One way flow control valve 2 14 Single acting cylinder 15 Double acting cylinder 16 FRL unit 17 Manifold 18 Connecting plates 19 Pneumatic motor 20 Vacuum generator 21 Proximity sensor (Inductive) 22 Limit switch (Electrical) 23 5/2 way Double solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel 26 Air Compressor — Compressor unit Suitable for Pressure: 8 bar, Delivery: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50 HZ, with pressure regulator and water	SF	OILLIAIS	BASIC PNEUMATIC
2 Quick Push-Pull connection 12 3 High Pressure Tubing (PU6) 5m 4 5/2 way lever operated valve 1 5 5/3 way Lever operated DC valve 1 6 Pressure Gauge 21/2" Dial 1 7 5/2 way Single Pilot operated 1 Direction control valve 8 5/2 way Double pilot operated 1 Direction control valve 9 AND Gate valve 1 1 Time delay valve 1 1 Time delay valve 1 1 1 Time delay valve 1 1 1 1 1 1 1 1 1		with Castel wheels	1
High Pressure Tubing (PU6) 5m		Quick Push-Pull connection	12
4 5/2 way lever operated valve 1 5 5/3 way Lever operated DC valve 1 6 Pressure Gauge 21/2" Dial 1 7 5/2 way Single Pilot operated Direction control valve 8 8 5/2 way Double pilot operated Direction control valve 9 9 AND Gate valve 1 10 OR Gate valve 1 11 Time delay valve NA 12 Quick exhaust valve 1 13 One way flow control valve 2 14 Single acting cylinder 1 15 Double acting cylinder 1 16 FRL unit 1 17 Manifold 1 18 Connecting plates 1 set 1 19 Pneumatic motor NA 20 Vacuum generator NA 21 Proximity sensor (Inductive) NA 22 Limit switch (Electrical) NA 23 5/2 way single solenoid operated direction control valve 2 24 5/2 way Double solenoid operated direction control valve 2 25 Electronic panel NA 26 Air Compressor – Compressor unit Suitable for Pressure : 8 bar, Delivery : 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V 50		High Pressure Tubing (PU6)	
5 5/3 way Lever operated DC valve 6 Pressure Gauge 21/2" Dial 7 5/2 way Single Pilot operated Direction control valve 8 5/2 way Double pilot operated Direction control valve 9 AND Gate valve 10 OR Gate valve 11 Time delay valve 12 Quick exhaust valve 13 One way flow control valve 2 14 Single acting cylinder 15 Double acting cylinder 16 FRL unit 17 Manifold 18 Connecting plates 19 Pneumatic motor NA 20 Vacuum generator 21 Proximity sensor (Inductive) 22 Limit switch (Electrical) 23 5/2 way single solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel 26 Air Compressor – Compressor unit Suitable for Pressure: 8 bar, Delivery: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V 50		5/2 way lever operated valve	1
7 5/2 way Single Pilot operated Direction control valve 8 5/2 way Double pilot operated Direction control valve 9 AND Gate valve 10 OR Gate valve 11 Time delay valve 12 Quick exhaust valve 13 One way flow control valve 2 14 Single acting cylinder 15 Double acting cylinder 16 FRL unit 17 Manifold 18 Connecting plates 19 Pneumatic motor 20 Vacuum generator 21 Proximity sensor (Inductive) 22 Limit switch (Electrical) 23 5/2 way single solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel 26 Air Compressor – Compressor unit Suitable for Pressure: 8 bar, Delivery: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V 50		5/3 way Lever operated DC valve	1
7 5/2 way Single Pilot operated Direction control valve 8 5/2 way Double pilot operated Direction control valve 9 AND Gate valve 10 OR Gate valve 11 Time delay valve NA 12 Quick exhaust valve 13 One way flow control valve 2 14 Single acting cylinder 15 Double acting cylinder 16 FRL unit 17 Manifold 18 Connecting plates 19 Pneumatic motor NA 20 Vacuum generator 21 Proximity sensor (Inductive) 22 Limit switch (Electrical) 23 5/2 way single solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel 26 Air Compressor – Compressor unit Suitable for Pressure: 8 bar, Delivery: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V 50		Pressure Gauge 21/2" Dial	1
8 5/2 way Double pilot operated Direction control valve 9 AND Gate valve 10 OR Gate valve 11 Time delay valve 12 Quick exhaust valve 13 One way flow control valve 2 14 Single acting cylinder 15 Double acting cylinder 16 FRL unit 17 Manifold 18 Connecting plates 19 Pneumatic motor NA 20 Vacuum generator NA 21 Proximity sensor (Inductive) NA 22 Limit switch (Electrical) NA 23 5/2 way single solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel NA 26 Air Compressor – Compressor unit Suitable for Pressure: 8 bar, Delivery: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50	(5/2 way Single Pilot operated	1
Direction control valve 9 AND Gate valve 10 OR Gate valve 11 Time delay valve 12 Quick exhaust valve 13 One way flow control valve 2 14 Single acting cylinder 15 Double acting cylinder 16 FRL unit 17 Manifold 1 18 Connecting plates 1 9 Pneumatic motor 20 Vacuum generator 21 Proximity sensor (Inductive) 22 Limit switch (Electrical) 23 5/2 way single solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel 26 Air Compressor – Compressor unit Suitable for Pressure: 8 bar, Delivery: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50	-	Direction control valve	
9 AND Gate valve 10 OR Gate valve 11 Time delay valve 12 Quick exhaust valve 13 One way flow control valve 2 14 Single acting cylinder 15 Double acting cylinder 16 FRL unit 17 Manifold 1 18 Connecting plates 19 Pneumatic motor 19 Preumatic motor 20 Vacuum generator 21 Proximity sensor (Inductive) 22 Limit switch (Electrical) 23 5/2 way single solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel 26 Air Compressor – Compressor unit Suitable for Pressure: 8 bar, Delivery: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V 50	8	5/2 way Double pilot operated	1
10 OR Gate valve 1 11 Time delay valve NA 12 Quick exhaust valve 1 13 One way flow control valve 2 14 Single acting cylinder 1 15 Double acting cylinder 1 16 FRL unit 1 17 Manifold 1 18 Connecting plates 1 set 1 19 Pneumatic motor NA 20 Vacuum generator NA 21 Proximity sensor (Inductive) NA 22 Limit switch (Electrical) NA 23 5/2 way single solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel NA 26 Air Compressor – Compressor unit Suitable for Pressure : 8 bar, Delivery : 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V 50	_		
11 Time delay valve 12 Quick exhaust valve 13 One way flow control valve 2 14 Single acting cylinder 15 Double acting cylinder 16 FRL unit 17 Manifold 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			1
12 Quick exhaust valve 1 13 One way flow control valve 2 14 Single acting cylinder 1 15 Double acting cylinder 1 16 FRL unit 1 17 Manifold 1 18 Connecting plates 1 set 1 19 Pneumatic motor NA 20 Vacuum generator NA 21 Proximity sensor (Inductive) NA 22 Limit switch (Electrical) NA 23 5/2 way single solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel NA 26 Air Compressor – Compressor unit Suitable for Pressure : 8 bar, Delivery : 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V 50			1
13 One way flow control valve 2 14 Single acting cylinder 15 Double acting cylinder 16 FRL unit 17 Manifold 18 Connecting plates 19 Pneumatic motor 20 Vacuum generator 21 Proximity sensor (Inductive) 22 Limit switch (Electrical) 23 5/2 way single solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel 26 Air Compressor – Compressor unit Suitable for Pressure: 8 bar, Delivery: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50		Time delay valve	NA
14 Single acting cylinder 15 Double acting cylinder 16 FRL unit 17 Manifold 18 Connecting plates 19 Pneumatic motor 20 Vacuum generator 21 Proximity sensor (Inductive) 22 Limit switch (Electrical) 23 5/2 way single solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel 26 Air Compressor – Compressor unit Suitable for Pressure: 8 bar, Delivery: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V 50		THE	1
15 Double acting cylinder 16 FRL unit 17 Manifold 18 Connecting plates 19 Pneumatic motor NA 20 Vacuum generator NA 21 Proximity sensor (Inductive) 22 Limit switch (Electrical) NA 23 5/2 way single solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel NA 26 Air Compressor – Compressor unit Suitable for Pressure: 8 bar, Delivery: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50		One way flow control valve	2
16 FRL unit 17 Manifold 18 Connecting plates 19 Pneumatic motor 20 Vacuum generator 21 Proximity sensor (Inductive) 22 Limit switch (Electrical) 23 5/2 way single solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel 26 Air Compressor – Compressor unit Suitable for Pressure: 8 bar, Delivery: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50		Single acting cylinder	1
17 Manifold 1 18 Connecting plates 1 set 19 Pneumatic motor NA 20 Vacuum generator NA 21 Proximity sensor (Inductive) NA 22 Limit switch (Electrical) NA 23 5/2 way single solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel NA 26 Air Compressor – Compressor unit Suitable for Pressure : 8 bar, Delivery : 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V 50			1
18 Connecting plates 19 Pneumatic motor 20 Vacuum generator 21 Proximity sensor (Inductive) 22 Limit switch (Electrical) 23 5/2 way single solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel 26 Air Compressor – Compressor unit Suitable for Pressure: 8 bar, Delivery: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50			1
19 Pneumatic motor 20 Vacuum generator NA 21 Proximity sensor (Inductive) NA 22 Limit switch (Electrical) NA 23 5/2 way single solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel NA 26 Air Compressor – Compressor unit Suitable for Pressure: 8 bar, Delivery: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50			1
20 Vacuum generator 21 Proximity sensor (Inductive) 22 Limit switch (Electrical) 23 5/2 way single solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel 26 Air Compressor – Compressor unit Suitable for Pressure: 8 bar, Delivery: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50		Connecting plates	1 set
21 Proximity sensor (Inductive) 22 Limit switch (Electrical) 23 5/2 way single solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel 26 Air Compressor – Compressor unit Suitable for Pressure: 8 bar, Delivery: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50			NA_
22 Limit switch (Electrical) 23 5/2 way single solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel 26 Air Compressor – Compressor unit Suitable for Pressure: 8 bar, Delivery: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50		Vacuum generator	NA
5/2 way single solenoid operated direction control valve 24 5/2 way Double solenoid operated direction control valve 25 Electronic panel Air Compressor – Compressor unit Suitable for Pressure: 8 bar, Delivery: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50			NA
direction control valve 5/2 way Double solenoid operated direction control valve Electronic panel Air Compressor – Compressor unit Suitable for Pressure : 8 bar, Delivery : 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50			NA
24 5/2 way Double solenoid operated direction control valve 25 Electronic panel NA 26 Air Compressor – Compressor unit Suitable for Pressure : 8 bar, Delivery : 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50	23	5/2 way single solenoid operated	NA
direction control valve 25 Electronic panel NA 26 Air Compressor – Compressor unit Suitable for Pressure: 8 bar, Delivery : 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50			
25 Electronic panel NA 26 Air Compressor – Compressor unit 1 Suitable for Pressure: 8 bar, Delivery: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50	24	5/2 way Double solenoid operated	NA
Air Compressor – Compressor unit Suitable for Pressure : 8 bar, Delivery : 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50			
Suitable for Pressure : 8 bar, Delivery : 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50			NA
: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50	26	Air Compressor – Compressor unit	1
: 50 lpm (or more), Reservoir Capacity: 24 litres (or more), 230V, 50		Suitable for Pressure : 8 bar, Delivery	
Capacity: 24 litres (or more), 230V, 50 HZ, with pressure regulator and water	-	: 50 lpm (or more), Reservoir	
HZ, with pressure regulator and water		Capacity: 24 litres (or more), 230V, 50	
I I I I I I I I I I I I I I I I I I I		HZ, with pressure regulator and water	
separator	7	separator	